

Wheel Features

Tread Material:	Nylon	Core Material:	High Strength PP
Bearing:	Annular Ball Bearing	Tread Hardness:	75D±3
Temperature:	-20°C~70°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Integral bearing, high concentricity
- ✔ Injection nylon, glue-free self lock structure, wearable and durable
- ✔ No deformation, anti-aging, endurable to humid environment
- ✔ With metal covers, thread-proof design
- ⚠ Hard wheel material, it may damage epoxy flooring
- ⚠ Wheel running may cause some noise






Rolling resistance	■■■■■	Excellent
Wear resistance	■■■■■	Excellent
Operating noise	■□□□	Acceptable
Floor surface preservation	■□□□	Acceptable

Bracket Features

- ✔ ON/OFF pedals, stable braking effect, easy to operate
- ✔ Bracket made of pressed steel plate, firm and strong
- ✔ Thickened top plate, resistant to compress which is hard to deform
- ✔ Reinforced riveted, close gap, high structural strength
- ✔ Dustproof ring effectively protects grease for long service life
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel width	Total height	Offset	Swivel Radius	Swivel Radius
3"	105 kg	75	30	108	34	71.5	116.5
3.5"	115 kg	88	32	120	32	76	116
4"	135 kg	100	32	135	32	82	116
5"	145 kg	125	32	160	32	94.5	121



[English]

Mounting Drawing




Plate Swivel





Plate Fixed



Threaded Stem

Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"	20A01-1018	20AB1-1018	20A3B-1018	20A04-1018	20A7B-1018
3.5"	20A10-1019	20AB2-1019	20A4B-1019	20A13-1019	20A8B-1019
4"	20A19-1020	20AB3-1020	20A5B-1020	20A22-1020	20A9B-1020
5"	20A28-1021	20AB4-1021	20A6B-1021	20A31-1021	20A1B-1021

Product Details

ON/OFF brake is easy to operate.



Fancy riveting has tight clearance, the structure is stable. Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours.



The arc wheel is easy to moving. The metal cover looks nice, and strong.

