

Wheel Features

Tread Material:	Supper PU	Core Material:	PP
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Injection polyurethane,glue-free self lock structureoil resistance,wear resistance
- ✔ Environmental protection,quiet,effectively protect the floor
- ⚠ Not water-proof,humid environment may accelerate aging of the wheel
- ⚠ Biodegradable material,recommended to use within 1 year of production for best performance





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good



Bracket Features

- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Top plate and ball tracks are quenched to enhance strength and prolong service life
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Environmentally friendly colour galvanized,salt spray test over 48 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	300 kg	100	45	145	34	84	148
5"	380 kg	125	48	165	38	101	151
6"	450 kg	150	50	190	44	119	154
8"	460 kg	200	50	240	54	154	173



Mounting Drawing



Product ID	Product Images	Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
		4"	35A60-0325	35A62-0325	35A61-0325	35A95-0325	35A96-0325
		5"	35A63-0326	35A65-0326	35A64-0326	35A97-0326	35A94-0326
		6"	35A66-0327	35A68-0327	35A67-0327	35A93-0327	35A98-0327
		8"	35A69-0328	35A71-0328	35A70-0328	35A99-0328	35AA1-0328

Product Details




ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.

Grease nipple is convenient for maintenance. Fancy riveted structure with gap tightly. Dust ring can protect the grease and dustproof effectively.

Quenched Ball Track has slight abrasion.

Non-quenched Ball Track' s abrasion and gap clearly.

Arc wheel surface, operation labor saving. Metal cover, nice appearance and anti-winding.



Comparison after 10000times Rotational test.

