

Wheel Features

Tread Material:	Rubber	Core Material:	Nylon
Bearing:	Ball Bearing	Tread Hardness:	75A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,injection bonding molding,high rebound
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With plastic covers,thread-proof design
- ⚠ Biodegradable rubber material,recommended to use within 3 year of production for best performance





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent



Bracket Features

- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Top plate and ball tracks are quenched to enhance strength and prolong service life
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	170 kg	100	45	145	34	84	148
5"	210 kg	125	50	165	38	101	151
6"	280 kg	150	50	190	44	119	154
8"	320 kg	200	50	240	54	154	173



Mounting Drawing



Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
4"	35A60-1714	35A62-1714	35A61-1714	35A95-1714	35A96-1714
5"	35A63-1408	35A65-1408	35A64-1408	35A97-1408	35A94-1408
6"	35A66-1409	35A68-1409	35A67-1409	35A93-1409	35A98-1409
8"	35A69-1410	35A71-1410	35A70-1410	35A99-1410	35AA1-1410

Product Details




ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Grease nipple is convenient for maintenance. Fancy riveted structure with gap tightly.

Quenched Ball Track has slight abrasion.



Non-quenched Ball Track's abrasion and gap clearly.



Natural rubber wheel surface, soft and high elasticity can protect the floor effectively. Metal cover, nice appearance and anti-winding.

Comparison after 10000times Rotational test.

