

Wheel Features

Tread Material:	TPR	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	80A±3
Temperature:	-15°C~60°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✓ 2 precision ball bearings, flexible rotation
- ✓ Advanced thermo-plastic rubber, silent running, elastic to protect floor
- ✓ Environmental protection, quiet, effectively protect the floor
- ⚠ Economical material with common load capacity





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent


Bracket Features

- ✓ Steel plate pressed and welded, firm and strong
- ✓ Reinforced riveted, close gap, high structural strength
- ✓ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours
- ✓ Easy to operate, convenient to release the brake
- ✓ Dustproof ring effectively protects grease for long service life

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	130 kg	100	50	145	34	84	148
5"	160 kg	125	50	165	38	101	151
6"	210 kg	150	50	190	44	119	154
8"	250 kg	200	50	240	54	154	173



Mounting Drawing



Product ID	Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Plate swivel brake	Plate swivel brake	Plate swivel brake
4"	35C01-1633	35C04-1633	35C20-1633	35C65-1633	35C03-1633	35C56-1633
5"	35C05-1634	35C08-1634	35C21-1634	35C66-1634	35C07-1634	35C57-1634
6"	35C09-1635	35C12-1635	35C22-1635	35C67-1635	35C11-1635	35C58-1635
8"	35C13-1636	35C16-1636	35C23-1636	35C68-1636	35C15-1636	35C59-1636

Product Details

Fancy riveting has tight clearance, the structure is stable and high strength.



Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours. The bracket is curved shape, nice appearance and high strength.



[English]

