

Wheel Features

| | | | |
|-----------------|--------------|-----------------|-----------|
| Tread Material: | Rubber | Core Material: | Cast Iron |
| Bearing: | Ball Bearing | Tread Hardness: | 85A±3 |
| Temperature: | -20°C~50°C | Running Speed: | 4km/h |

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,vulcanized,high rebound
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With metal covers,thread-proof design
- ✔ Painted,anti-rust and anti-corrosion
- ⚠ Biodegradable rubber material,recommended to use within 3 year of production for best performance





| | | |
|----------------------------|-----------|-----------|
| Rolling resistance | ■ ■ ■ □ □ | Good |
| Wear resistance | ■ ■ ■ ■ □ | Very good |
| Operating noise | ■ ■ ■ ■ ■ | Excellent |
| Floor surface preservation | ■ ■ ■ ■ ■ | Excellent |


Bracket Features

- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Double springs plus cushion block design,large cushion range,outstanding shock absorption performance
- ✔ Powder spray treatment,superior anti-rust and anti-corrosion performance,salt spray test over 72 hours
- ⚠ Wheel brake only,without direction lock function

| Parameter (mm) | Capacity | Wheel Dia. | Wheel Width | Total Height | Offset | Swivel Radius | Swivel Radius |
|-------------------|----------|------------|-------------|--------------|--------|---------------|---------------|
| Wheel Size | Capacity | Wheel Dia. | Wheel Width | Total Height | Offset | Swivel Radius | Swivel Radius |
| 5" | 300 kg | 125 | 48 | 195 | 60 | 122.5 | 185 |
| 6" | 350 kg | 150 | 48 | 207 | 60 | 135 | 193 |



Mounting Drawing



| Product ID |  |  |  |
|----------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Product Images | | | |
| Wheel Size | Plate swivel | Plate fixed | Plate swivel brake |
| 5" | 45E01-1146 | 45E02-1146 | 45E03-1146 |
| 6" | 45E04-1147 | 45E05-1147 | 45E06-1147 |

Product Details

ON/OFF brake is easy to operate.



Double spring and polyurethane block design, large retraction stroke, shock absorption performance is better, can effectively buffer and ensure balance and stability.



Double-welded, strong and robust. Dust ring can effectively protect the dust and grease lubrication.



The soft natural rubber wheel has high rebound properties to protect the floor. Iron cover is nice appearance and anti-winding.



[English]

