

Wheel Features

Tread Material:	PU	Core Material:	High Strength PP
Bearing:	Single Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Precision ball bearing, flexible rotation
- ✔ Injection polyurethane, glue-free self lock structure, oil resistance, wear resistance
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ High temperature and humidity may shorten service life





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good

Bracket Features




- ✔ Easy to operate, convenient to release the brake
- ✔ Direction brake to stop swiveling
- ✔ Spindle equipped with precision bearing, quiet and flexible
- ✔ Bracket made of pressed steel plate, firm and strong
- ✔ Galvanized, salt spray test over 48 hours
- ✔ This product has passed TUV certification. Utility model patent owned, protected by intellectual property law.

Parameter (mm)	KG						
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	100 kg	100	32	144	30	80	105
5"	125 kg	120	32	180	38	100	132
Wheel Size	Total height	Total height					
4"	142	134					
5"	188	167					



[English]

Mounting Drawing



Product ID							
Product Images							
Wheel Size	Plate swivel	Plate single function brake	Plate dual function brake	Threaded stem	Threaded stem single function brake	Threaded stem dual function brake	Stem of swivel
4"	80C04-1704	80C05-1704	80C06-1704	80C13-1704	80C14-1704	80C15-1704	80C22-1704
5"	80C07-1705	80C08-1705	80C09-1705	80C16-1705	80C17-1705	80C18-1705	80C25-1705
Product ID							
Product Images							
Wheel Size	Stem single function brake	Stem dual function brake					
4"	80C23-1704	80C24-1704					
5"	80C26-1705	80C27-1705					

Product Details



Double pedals, with directional function.

This series of products are certified by TUV.



The strength of shell seam is upgraded, beautiful and durable.

